



an AIR LIQUIDE Group Company

# SAFETY DATA SHEET

Page : 1 / 4

Revised edition no : 1

Date : 15 / 9 / 2010

Supersedes : 0 / 0 / 0

## G26 fuel gas test mixture 7% propane,13% nitrogen in methane

8578



F+ : Extremely flammable



2.1 : Flammable gases

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

Trade name : G26 fuel gas test mixture 7% propane,13% nitrogen in methane  
 SDS Nr : 8578  
 Company identification : **AGU** Ltd.  
 Y. d. [ | ] a. A. d. c  
 P. W. G. E. Y  
 United Kingdom  
 Emergency telephone number : 011 1 411 111

### SECTION 3. Composition/information on ingredients

Mixture.  
 Components : This product is hazardous.

Substance name	Contents	CAS No EC No Index No Registration no	Classification(DSD)	Classification(CLP)
Propane	7 %	74-98-6 200-827-9 601-003-00-5 01-2119486944-21-	F+; R12	Flam. Gas 1 (H220) Press. Gas Liquefied (H280)
Nitrogen	13 %	7727-37-9 231-783-9 ----- *1	Not classified (DSD)	Press. Gas Compressed (H280)
Methane	80 %	74-82-8 200-812-7 601-001-00-4 * 1	F+; R12	Flam. Gas 1 (H220) Press. Gas Compressed (H280)

### SECTION 4. First aid measures

#### First aid measures

- Inhalation : In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/ consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- Ingestion : Ingestion is not considered a potential route of exposure.

**G26 fuel gas test mixture 7% propane, 13% nitrogen in methane**

**8578**

**SECTION 5. Firefighting measures**

**Extinguishing media**

- Suitable extinguishing media : All known extinguishants can be used.

**Specific hazards** : Exposure to fire may cause containers to rupture/explode.

**Hazardous combustion products** : None.

**Specific methods** : Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire. If possible, stop flow of product. Move away from the container and cool with water from a protected position.

**Special protective equipment for fire fighters** : Do not enter fire area without proper protective equipment, including respiratory protection.

**Flammable class** : Extremely flammable.

**SECTION 6. Accidental release measures**

**Personal precautions** : Evacuate area.  
Ensure adequate air ventilation.  
Eliminate ignition sources.

Try to stop release.

**Clean up methods** : Ventilate area.

**SECTION 7. Handling and storage**

**Handling** : Keep away from ignition sources (including static discharges).  
Open valve slowly to avoid pressure shock.  
Suck back of water into the container must be prevented.  
Do not allow backfeed into the container.  
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.  
Refer to supplier's container handling instructions.

**Storage** : Segregate from oxidant gases and other oxidants in store.  
Keep container below 50°C in a well ventilated place.

**SECTION 8. Exposure controls/personal protection**

**8.2. Exposure controls**

**Personal protection** : Do not smoke while handling product.  
Ensure adequate ventilation.

**SECTION 9. Physical and chemical properties**

**Physical state at 20°C / 101.3kPa** : Compressed gas.  
**Colour** : Colourless.  
**Odour** : Hydrocarbon.  
**Relative density, gas (air=1)** : Lighter or similar to air.  
**Solubility in water [mg/l]** : No reliable data available.

**G26 fuel gas test mixture 7% propane, 13% nitrogen in methane**

**8578**

**SECTION 10. Stability and reactivity**

**Stability and reactivity** : Can form explosive mixture with air.  
May react violently with oxidants.

**SECTION 11. Toxicological information**

**Toxicity information** : No known toxicological effects from this product.

**SECTION 12. Ecological information**

**Effect on ozone layer** : None.

**SECTION 13. Disposal considerations**

**General** : Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into any place where its accumulation could be dangerous. Contact supplier if guidance is required.

**Disposal method** : Consult supplier for specific recommendations.

**SECTION 14. Transport information**

**UN number** : 1954  
**H.I. nr** : 23  
**UN proper shipping name** : COMPRESSED GAS, FLAMMABLE, N.O.S. (Methane, Propane)  
**Transport hazard class(es)** : 2  
**Classification code** : 1 F  
**Labelling ADR** : 2.1 : Flammable gases  
**ADR/RID**  
**Other transport information** : Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.  
 Before transporting product containers:  
 - Ensure that containers are firmly secured.  
 - Ensure cylinder valve is closed and not leaking.  
 - Ensure valve outlet cap nut or plug (where provided) is correctly fitted.  
 - Ensure valve protection device (where provided) is correctly fitted.  
 - Ensure there is adequate ventilation.  
 - Compliance with applicable regulations.

**SECTION 16. Other information**

**Training advice** : Ensure operators understand the flammability hazard. The hazard of asphyxiation is often overlooked and must be stressed during operator training. Receptacle under pressure. Ensure all national/local regulations are observed.

**Note** : This Safety Data Sheet has been established in accordance with the applicable European Union legislation.

**DISCLAIMER OF LIABILITY** : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.



an AIR LIQUIDE Group Company

# SAFETY DATA SHEET

Page : 4 / 4

Revised edition no : 1

Date : 15 / 9 / 2010

Supersedes : 0 / 0 / 0

**G26 fuel gas test mixture 7% propane, 13% nitrogen in methane**

**8578**

## SECTION 16. Other information (continued)

End of document