


ARCAL™ M24



Applications

MAG welding

Transport information

Compressed gases

Proper shipping name	Compressed gas, N.O.S. (Argon, Carbon Dioxide)
UN-Nr	1956
ADR/RID	Class 2
	Classification code 1A



Safety Data Sheets

Compressed gas : SDS 01208

Access: https://drive.google.com/open?id=1v7Hjib41Y88qrETQFfqnC1-lu6dCebsX&usp=drive_copy

Physical information

Relative density:	
Relative density, gas	Heavier than air
Colour	Colorless
Odor	Odorless

Properties

Hazards identification: Contains gas under pressure; may explode under the effect of heat. Asphyxiant in high concentrations.

Flammability range: Inert; non-flammable



Cylinder equipment

Shoulder colour:
Bright green (RAL 6018)



Product Specifications

Components (% Vol. abs)			Impurities (ppm v/v)		Supply mode	Packaging size	Pressure	Capacity	Product reference
O ₂	2%	± 0.5%	H ₂ O (5 bar)	40	Cylinder	33L QLIXBI	300 bar	10,7 m3	I2578L33J3A001
CO ₂	12%	± 1.2%	N ₂	200	Cylinder	50L	300 bar	16,2 m3	I2578L50J3A001
Ar	Balance								

Disclaimer

The information contained in this product sheet is based on the technical information and experience currently available to AIR LIQUIDE.

Users are responsible for the use or consequences of use of the information contained in this Product sheet. AIR LIQUIDE makes no warranties regarding the information contained in this document.

The users are responsible for ensuring compliance with regulations (national or European), insurance requirements or codes. Moreover the user is obliged to carry out own tests and checks regarding the suitability of the products and data described herein for his individual purposes and applications.

It is up to users of this document to ensure that they have the latest edition.

The trademarks, trade names, logos or other indications of origin displayed in this Product sheet are registered and unregistered trademarks of AIR LIQUIDE.

It is strictly forbidden to copy or reproduce some or all parts of this Product sheet.