

Chemical formula 1 N2 Registration-No. : Listed in Annex IV / V REACH, exempted from registration. Use : Industrial and professional. Perform risk assessment prior to use. Company identification : Energas Ltd. Westmorland Street, Hull HU2 0HX, United Kingdom E-Mail address (competent person): : mark.nugent@energas.co.uk Emergency telephone number : 01482 329333

2 Hazards identification

Classification of the substance or mixture

Hazard Class and Category Code Regulation EC 1272/2008 (CLP)	
 Physical hazards 	: Gases under pressure - Compressed gas - Warning (H280)
Classification EC 67/548 or EC 1999/ 45	 Not included in Annex VI. Not classified as dangerous preparation/substance. No EC labelling required.

Label elements

Labelling Regulation EC 1272/2008 (CLP) • Hazard pictograms





Page : 2 / 5

Revised edition no : 0

Date : 26 / 08 / 2014

Supersedes : 0 / 0 / 0

Fresh Gas - Nitrogen

SDS_089A_CLP

Hazard pictograms code	: GHS04
• Signal word	: Warning
Hazard statements	: H280 : Contains gas under pressure; may explode if heated.
Precautionary statements	
- Storage	: P403 : Store in a well-ventilated place.
Labelling EC 67/548 or EC 1999/45	
Symbol(s)	: None.
R Phrase(s)	: None.
S Phrase(s)	: None.
Other hazards	
Other hazards	: Asphyxiant in high concentrations.
B Composition/information on ingred	lients
Substance / Preparation	: Substance.
Substance name	Contents CAS No EC No Index No Registration no Classification 100 % 7727-37-9 231-783-9 NOTE 1
Full text of R-phrases see chapter 16	
First aid measures	
First aid measures	
First aid measures - Inhalation	 In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- Inhalation	mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if
- Inhalation	mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if
- Inhalation	mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- Inhalation 5 Fire-fighting measures 5 Specific hazards Hazardous combustion products	 mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped. : Exposure to fire may cause containers to rupture/explode.
- Inhalation 5 Fire-fighting measures Specific hazards	 mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped. : Exposure to fire may cause containers to rupture/explode.
 Inhalation 5 Fire-fighting measures Specific hazards Hazardous combustion products Extinguishing media 	 mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped. Exposure to fire may cause containers to rupture/explode. None.



Page : 3 / 5

Revised edition no : 0 Date : 26 / 08 / 2014

Fresh Gas - Nitrogen

SDS_089A_CLP

Supersedes : 0 / 0 / 0

Personal precautions	: Evacuate area. Wear self-contained breathing apparatus when entering area unless atmosphere i proved to be safe.
	Ensure adequate air ventilation.
Environmental precautions	: Try to stop release.
Clean up methods	: Ventilate area.
7 Handling and storage	
Handling	: Suck back of water into the container must be prevented. Do not allow backfeed into the container.
	Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Refer to supplier's container handling instructions.
Storage	: Keep container below 50°C in a well ventilated place.
8 Exposure controls/personal prote	ection
Personal protection	: Ensure adequate ventilation.
9 Physical and chemical properties	
Physical state at 20 °C	: Gas.
Colour	: Colourless gas.
Odour	: No odour warning properties.
Molecular weight	: 28
Melting point [°C]	: -210
Boiling point [°C]	: -196
Critical temperature [°C]	: -147
Vapour pressure [20°C]	: Not applicable.
Relative density, gas (air=1)	: 0.97
Relative density, liquid (water=1)	: Not applicable.
Solubility in water [mg/l]	: 20
10 Stability and reactivity	
Hazardous decomposition products	s : None.
Chemical stability	: Stable under normal conditions.
11 Toxicological information	
Toxicity information	: No known toxicological effects from this product.
12 Ecological information	



Page : 4 / 5

Revised edition no : 0

Date : 26 / 08 / 2014 Supersedes : 0 / 0 / 0

Fresh Gas - Nitrogen

SDS_089A_CLP

General	: Do not discharge into any place where its accumulation could be dangerous. To atmosphere in a well ventilated place. Contact supplier if guidance is required.
Transport information	
UN number	: 1066
Labelling ADR, IMDG, IATA	
	: 2.2 : Non flammable, non toxic gas.
Land transport	
ADR/RID	
H.I. nr	: 20
UN proper shipping name	: NITROGEN, COMPRESSED
Transport hazard class(es)	: 2
- ADR/RID Classification code	: 1 A
- Packing Instruction(s) - General	: P200
- Tunnel Restriction	: E : Passage forbidden through tunnels of category E.
Sea transport	
- IMO-IMDG code	
 Proper shipping name 	: NITROGEN, COMPRESSED
• Class	: 2.2
- IMO Packing group	: P200
- Emergency Schedule (EmS) - Fire	: F-C
- Emergency Schedule (EmS) - Spillage	: S-V
- Instructions - Packing	: P200
Air transport	
- ICAO/IATA	
 Proper shipping name 	: NITROGEN, COMPRESSED
• Class	: 2.2
 Passenger and Cargo Aircraft 	:
- Packing instruction	: 200
Cargo Aircraft only	:
- Packing instruction	: 200
Ensure vehicle driver is aware of the pot	ad space is not separated from the driver's compartment. tential hazards of the load and knows what to do in the event of an accident or an
emergency.	
Before transporting product containers :	ad .
 Ensure that containers are firmly secur Ensure cylinder valve is closed and no 	

Westmorland Street, Hull HU2 0HX, United Kingdom



Page : 5 / 5

Revised edition no : 0

Date : 26 / 08 / 2014

Supersedes : 0 / 0 / 0

Fresh Gas - Nitrogen

SDS_089A_CLP

14 Transport information (continued)

- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.

- Ensure valve protection device (where provided) is correctly fitted.
- Ensure there is adequate ventilation.
- Compliance with applicable regulations.

15 Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture
 : Ensure all national/local regulations are observed.

 Seveso regulation 96/82/EC
 : Not covered.

16 Other information

Asphyxiant in high concentrations.

Keep container in a well-ventilated place.

Do not breathe the gas.

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws.

DISCLAIMER OF LIABILITY

 Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.
 Details given in this document are believed to be correct at the time of going to press. Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

End of document