

HELIWELD 6

according to Regulation (EU) 2015/830 Reference number: SDS 01176 Issue date: 2/19/2020 Revision date: 8/25/2022 Version: 2.0

Warning



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SDS no : SDS 01176

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use.

Test gas/Calibration gas.

Contact supplier for more information on uses.

Uses advised against : Consumer use.

1.3. Details of the supplier of the safety data sheet

Energas Ltd Westmorland Street Hull, HU2 0HX

1.4. Emergency telephone number

Emergency telephone number : 01675 462695 (Available 24/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards Gases under pressure : Compressed gas H280

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :

GHS04

Signal word (CLP) : Warning

Hazard statements (CLP) : H280 - Contains gas under pressure; may explode if heated.

Precautionary statements (CLP)

- Storage : P410+P403 - Protect from sunlight. Store in a well-ventilated place.

2.3. Other hazards

Asphyxiant in high concentrations.

SECTION 3: Composition/information on ingredients

3.1. Substances Not applicable



HELIWELD 6

according to Regulation (EU) 2015/830 Reference number: SDS 01176

3.2. Mixtures

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|--------|--|----|---|
| Argon | CAS-No.: 7440-37-1 EC-No.: 231-147-0 EC Index-No.: REACH-no: *1 | 70 | Press. Gas (Comp.), H280 |
| Helium | CAS-No.: 7440-59-7 EC-No.: 231-168-5 EC Index-No.: REACH-no: *1 | 30 | Press. Gas (Comp.), H280 |

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep

victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing

stopped.

Skin contact
 Eye contact
 Adverse effects not expected from this product.
 Adverse effects not expected from this product.

- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of

mobility/consciousness. Victim may not be aware of asphyxiation.

See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.

- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products : None.

5.3. Advice for firefighters

Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat

radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering

sewers and drainage systems. If possible, stop flow of product.

Use water spray or fog to knock down fire fumes if possible.

Move containers away from the fire area if this can be done without risk.

^{*1:} Listed in Annex IV / V REACH, exempted from registration.

^{*3:} Registration not required: Substance manufactured or imported < 1t/y.



HELIWELD 6

according to Regulation (EU) 2015/830 Reference number: SDS 01176

Special protective equipment for fire fighters

: In confined space use self-contained breathing apparatus.

Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves

for firefighters.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Try to stop release.

Evacuate area.

Wear self-contained breathing apparatus when entering area unless atmosphere is proved

to be safe.

Ensure adequate air ventilation.

Act in accordance with local emergency plan.

Stay upwind.

Oxygen detectors should be used when asphyxiating gases may be released.

6.2. Environmental precautions

Try to stop release.

6.3. Methods and material for containment and cleaning up

Ventilate area.

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safe use of the product

: Do not breathe gas.

Avoid release of product into atmosphere.

The product must be handled in accordance with good industrial hygiene and safety procedures.

Only experienced and properly instructed persons should handle gases under pressure.

Consider pressure relief device(s) in gas installations.

Ensure the complete gas system was (or is regularily) checked for leaks before use.

Do not smoke while handling product.

Use only properly specified equipment which is suitable for this product, its supply pressure

and temperature. Contact your gas supplier if in doubt.

Avoid suck back of water, acid and alkalis.



HELIWELD 6

according to Regulation (EU) 2015/830 Reference number: SDS 01176

Safe handling of the gas receptacle

: Refer to supplier's container handling instructions.

Do not allow backfeed into the container.

Protect containers from physical damage; do not drag, roll, slide or drop.

When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.

Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.

If user experiences any difficulty operating valve discontinue use and contact supplier.

Never attempt to repair or modify container valves or safety relief devices.

Damaged valves should be reported immediately to the supplier.

Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the content of the container.

Suck back of water into the container must be prevented.

Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion.

Container valve guards or caps should be in place.

Containers should be stored in the vertical position and properly secured to prevent them

from falling over.

Stored containers should be periodically checked for general condition and leakage.

Keep container below 50°C in a well ventilated place.

Store containers in location free from fire risk and away from sources of heat and ignition.

Keep away from combustible materials.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL (Occupational Exposure Limits) : None available.

DNEL (Derived-No Effect Level) : None available.

PNEC (Predicted No-Effect Concentration) : None available.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Systems under pressure should be regularily checked for leakages.

Oxygen detectors should be used when asphyxiating gases may be released. Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.

The following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected.

Eye/face protection
 Wear safety glasses with side shields.

Standard EN 166 - Personal eye-protection - specifications.

Skin protection



HELIWELD 6

according to Regulation (EU) 2015/830 Reference number: SDS 01176

- Hand protection : Wear working gloves when handling gas containers.

Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.

: Wear safety shoes while handling containers.

Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

· Respiratory protection : Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

face mask.

Consult respiratory device supplier's product information for the selection of the appropriate

device.

Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be

used in oxygen-deficient atmospheres.

 Thermal hazards None in addition to the above sections.

8.2.3. Environmental exposure controls

None necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

- Other

- Physical state at 20°C / 101.3kPa : Gas

- Colour Mixture contains one or more component(s) which have the following colour(s):

Colourless

Odour Odourless.

Odour threshold is subjective and inadequate to warn of overexposure.

рΗ Not applicable for gases and gas mixtures.

Melting point / Freezing point Not applicable for gas mixtures. Boiling point Not applicable for gas mixtures.

Flash point Not applicable for gases and gas mixtures.

Flammability Non flammable. Lower explosion limit Not available Upper explosion limit Not available Vapour pressure [20°C] : Not applicable. Vapour pressure [50°C] Not applicable. Not applicable Density Vapour density Not applicable. Relative density, liquid (water=1) Not applicable

Lighter or similar to air. Relative density, gas (air=1)

Water solubility Not available

Partition coefficient n-octanol/water (Log Kow) : Not applicable for gas mixtures.

Auto-ignition temperature : Non flammable. Decomposition temperature : Not applicable.

Viscosity, kinematic : No reliable data available.

Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Explosive properties : Not applicable. Oxidising properties : Not applicable.

9.2.2. Other safety characteristics

Molar mass : Not applicable for gas mixtures.

Evaporation rate : Not applicable for gases and gas mixtures.

Other data None.

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.



HELIWELD 6

according to Regulation (EU) 2015/830 Reference number: SDS 01176

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None.

Reactivity : None.

10.4. Conditions to avoid

Avoid moisture in installation systems.

10.5. Incompatible materials

For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not

be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Toxicological effects not expected from this product if occupational exposure limit values are

not exceeded.

: No known effects from this product. Skin corrosion/irritation : No known effects from this product. Serious eye damage/irritation No known effects from this product. Respiratory or skin sensitisation : No known effects from this product. Germ cell mutagenicity : No known effects from this product. Carcinogenicity : No known effects from this product. Toxic for reproduction: Fertility : No known effects from this product. Toxic for reproduction: unborn child : No known effects from this product. STOT-single exposure

STOT-repeated exposure : No known effects from this product.

Aspiration hazard : Not applicable for gases and gas mixtures.

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Assessment : No ecological damage caused by this product.

EC50 48h - Daphnia magna [mg/l] : No data available. EC50 72h - Algae [mg/l] : No data available. LC50 96 h - Fish [mg/l] : No data available.

| Helium (7440-59-7) | | |
|---------------------------------|--------------------|--|
| EC50 48h - Daphnia magna [mg/l] | No data available. | |
| EC50 72h - Algae [mg/l] | No data available. | |
| LC50 96 h - Fish [mg/l] | No data available. | |

| Argon (7440-37-1) | | |
|---------------------------------|--------------------|--|
| EC50 48h - Daphnia magna [mg/l] | No data available. | |



HELIWELD 6

according to Regulation (EU) 2015/830 Reference number: SDS 01176

| Argon (7440-37-1) | | |
|-------------------------|--------------------|--|
| EC50 72h - Algae [mg/l] | No data available. | |
| LC50 96 h - Fish [mg/l] | No data available. | |

12.2. Persistence and degradability

Assessment : No ecological damage caused by this product.

12.3. Bioaccumulative potential

Assessment : No data available.

12.4. Mobility in soil

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.

Partition into soil is unlikely.

12.5. Results of PBT and vPvB assessment

: Not classified as PBT or vPvB. Assessment

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Other adverse effects : No known effects from this product.

Effect on the ozone layer : None.

Effect on global warming : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

May be vented to atmosphere in a well ventilated place.

Do not discharge into any place where its accumulation could be dangerous.

Return unused product in original container to supplier.

List of hazardous waste codes (from Commission

Decision 2000/532/EC as amended)

16 05 05: Gases in pressure containers other than those mentioned in 16 05 04.

13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN

UN-No. : 1956

14.2. UN proper shipping name

: COMPRESSED GAS, N.O.S. (Argon, Helium) Transport by road/rail (ADR/RID) : Compressed gas, n.o.s. (Argon, Helium) Transport by air (ICAO-TI / IATA-DGR) : COMPRESSED GAS, N.O.S. (Argon, Helium) Transport by sea (IMDG)

14.3. Transport hazard class(es)

Labelling

2.2: Non-flammable, non-toxic gases.

Energas Ltd.

EN (English)



HELIWELD 6

according to Regulation (EU) 2015/830 Reference number: SDS 01176

Transport by road/rail (ADR/RID)

Class : 2
Classification code : 1A
Hazard identification number : 20

Tunnel Restriction : E - Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 2.2

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.2
Emergency Schedule (EmS) - Fire : F-C
Emergency Schedule (EmS) - Spillage : S-V

14.4. Packing group

Transport by road/rail (ADR/RID) : Not applicable
Transport by air (ICAO-TI / IATA-DGR) : Not applicable
Transport by sea (IMDG) : Not applicable

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.
Transport by air (ICAO-TI / IATA-DGR) : None.
Transport by sea (IMDG) : None.

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P200

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : 200.
Cargo Aircraft only : 200.
Transport by sea (IMDG) : P200

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's

compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in

the event of an accident or an emergency.
Before transporting product containers:
- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure valve is closed and not leaking.

- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.

- Ensure valve protection device (where provided) is correctly fitted.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Restrictions on use : None.

Contains no substance on the REACH candidate list : Ensure all national/local regulations are observed.

Other information, restriction and prohibition

regulations

Seveso Directive: 2012/18/EU (Seveso III) : Not covered.

National regulations

No additional information available

15.2. Chemical safety assessment

A CSA does not need to be carried out for this product.

Energas Ltd. Westmorland Street HU2 0HX Hull, 0044 1482 329333 8/9



HELIWELD 6

according to Regulation (EU) 2015/830 Reference number: SDS 01176

SECTION 16: Other information

Indication of changes : Safety data sheet in accordance with commission regulation (EU) No 2020/878. Abbreviations and acronyms : ATE - Acute Toxicity Estimate CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006 EINECS - European Inventory of Existing Commercial Chemical Substances CAS# - Chemical Abstract Service number LC50 - Lethal Concentration to 50 % of a test population RMM - Risk Management Measures PBT - Persistent, Bioaccumulative and Toxic vPvB - Very Persistent and Very Bioaccumulative STOT- SE: Specific Target Organ Toxicity - Single Exposure CSA - Chemical Safety Assessment EN - European Standard **UN - United Nations** ADR - European Agreement concerning the International Carriage of Dangerous Goods by IATA - International Air Transport Association IMDG code - International Maritime Dangerous Goods RID - Regulations concerning the International Carriage of Dangerous Goods by Rail WGK - Water Hazard Class STOT - RE: Specific Target Organ Toxicity - Repeated Exposure Training advice The hazard of asphyxiation is often overlooked and must be stressed during operator For more guidance, refer to EIGA SL 01 "Dangers of Asphyxiation", downloadable at http://www.eiga.eu.. Further information Classification using data from databases maintained by the European Industrial Gases Association (EIGA). Data is maintained in EIGA doc 169: 'Classification and Labelling Guide', downloadable at : http://www.eiga.eu. Classification in accordance with the procedures and calculation methods of Regulation

| Full text of H- and EUH-statements | | |
|------------------------------------|---|--|
| H280 | Contains gas under pressure; may explode if heated. | |
| Press. Gas (Comp.) | Gases under pressure : Compressed gas | |

(EC) 1272/2008 (CLP).

| Full text of H- and EUH-statements | |
|------------------------------------|---|
| H280 | Contains gas under pressure; may explode if heated. |
| Press. Gas (Comp.) | Gases under pressure : Compressed gas |

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document

DISCLAIMER OF LIABILITY