

MIGWELD UNIVERSAL

according to Regulation (EU) 2015/830 Reference number: SDS 01115 Issue date: 8/1/2019 Revision date: 8/25/2022 Version: 2.0

Warning



SECTION 1: Identifie	SECTION 1: Identification of the substance/mixture and of the company/undertaking		
1.1. Product identifier			
SDS no	:	: SDS 01115	
1.2. Relevant identified u	ses of the substance or m	nixture and uses advised against	
Relevant identified uses		 Industrial and professional uses. Perform risk assessment prior to use. Test gas/Calibration gas. Laboratory use. Contact supplier for more information on uses. 	
Uses advised against	:	Consumer use.	
1.3. Details of the supplie	er of the safety data sheet		
Energas Ltd Westmorland Street Hull, HU2 0HX			
1.4. Emergency telephon	<u>e number</u>		
Emergency telephone num	ber :	: 01675 462695 (Available 24/7)	
SECTION 2: Hazard	s identification		
2.1. Classification of the	substance or mixture		
Classification according	to Regulation (EC) No. 127	72/2008 [CLP]	
Physical hazards	Gases under pressure : Co	ompressed gas H280	
2.2. Label elements			
Labelling according to R	egulation (EC) No. 1272/20	008 [CLP]	
Hazard pictograms (CLP)	:	GHS04	
Signal word (CLP)	:	: Warning	
Hazard statements (CLP) Precautionary statements		H280 - Contains gas under pressure; may explode if heated.	
- Storage	:	P410+P403 - Protect from sunlight. Store in a well-ventilated place.	
2.3. Other hazards			
		Asphyxiant in high concentrations.	

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable



MIGWELD UNIVERSAL

according to Regulation (EU) 2015/830 Reference number: SDS 01115

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Argon	CAS-No.: 7440-37-1 EC-No.: 231-147-0 EC Index-No.: REACH-no: *1	85	Press. Gas (Comp.), H280
Carbon dioxide	CAS-No.: 124-38-9 EC-No.: 204-696-9 EC Index-No.: REACH-no: *1	13.5	Press. Gas (Liq.), H280
Oxygen	CAS-No.: 7782-44-7 EC-No.: 231-956-9 EC Index-No.: 008-001-00-8 REACH-no: *1	1.5	Ox. Gas 1, H270 Press. Gas (Comp.), H280

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*3: Registration not required: Substance manufactured or imported < 1t/y.

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation	: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact	: Adverse effects not expected from this product.
- Eye contact	: Adverse effects not expected from this product.
- Ingestion	: Ingestion is not considered a potential route of exposure.
4.2. Most important symptoms and effects, both acute and delayed	

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
 Suitable extinguishing media Unsuitable extinguishing media 	: Water spray or fog. : Do not use water jet to extinguish.	
5.2. Special hazards arising from the substance or mixture		
Specific hazards Hazardous combustion products	Exposure to fire may cause containers to rupture/explode.None.	



MIGWELD UNIVERSAL

according to Regulation (EU) 2015/830 Reference number: SDS 01115

5.3. Advice for firefighters	
Specific methods	 Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Move containers away from the fire area if this can be done without risk.
Special protective equipment for fire fighters	 Use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Try to stop release. Evacuate area. Monitor concentration of released product. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Act in accordance with local emergency plan. Stay upwind.	
6.2. Environmental precautions		
	Try to stop release.	
6.3. Methods and material for containment and cleaning up		
	Ventilate area.	
6.4. Reference to other sections	See also sections 8 and 13.	
SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Safe use of the product	: Do not breathe gas.	

Avoid release of product into atmosphere. The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularily) checked for leaks before use. Do not smoke while handling product. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.



MIGWELD UNIVERSAL

according to Regulation (EU) 2015/830 Reference number: SDS 01115

Safe handling of the gas receptacle	: Refer to supplier's container handling instructions.
	Do not allow backfeed into the container.
	Protect containers from physical damage; do not drag, roll, slide or drop.
	When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
	Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
	If user experiences any difficulty operating valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices.
	Damaged valves should be reported immediately to the supplier.
	Keep container valve outlets clean and free from contaminants particularly oil and water.
	Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
	Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another.
	Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the content of the container.
	Containers should be stored in the vertical position and properly secured to prevent them from falling over.
7.2. Conditions for safe storage, including	any incompatibilities
	Observe all regulations and local requirements regarding storage of containers.
	Containers should not be stored in conditions likely to encourage corrosion.
	Container valve guards or caps should be in place.
	Containers should be stored in the vertical position and properly secured to prevent them from falling over.
	Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place.
	Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Carbon dioxide (124-38-9)	
United Kingdom - Occupational Exposure Limits	
Local name	Carbon dioxide
WEL TWA (OEL TWA) [1]	9150 mg/m³
WEL TWA (OEL TWA) [2]	5000 ppm
WEL STEL (OEL STEL)	27400 mg/m ³
WEL STEL (OEL STEL) [ppm]	15000 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Ensure exposure is below occupational exposure limits (where available). Oxygen detectors should be used when asphyxiating gases may be released. Consider the use of a work permit system e.g. for maintenance activities.



MIGWELD UNIVERSAL

according to Regulation (EU) 2015/830 Reference number: SDS 01115

8.2.2. Individual protection measures, e.g. personal protective equipment

	A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:
	PPE compliant to the recommended EN/ISO standards should be selected.
Eye/face protection	: Wear safety glasses with side shields.
	Standard EN 166 - Personal eye-protection - specifications.
Skin protection	
- Hand protection	: Wear working gloves when handling gas containers.
	Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.
- Other	: Wear safety shoes while handling containers.
	Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
Respiratory protection	: Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
	Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be
	used in oxygen-deficient atmospheres.
Thermal hazards	: None necessary.
8.2.3. Environmental exposure controls	
	Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Appearance		
 Physical st 	ate at 20°C / 101.3kPa	: Gas
- Colour		: Mixture contains one or more component(s) which have the following colour(s
		Colourless.
Odour		: Odourless.
		Odour threshold is subjective and inadequate to warn of overexposure.
		Odour threshold is subjective and inadequate to warn of overexposure.
рН		: Not applicable for gas mixtures.
Melting point / I	Freezing point	: Not applicable for gas mixtures.
Boiling point		: Not applicable for gas mixtures.
Flash point		: Not applicable for gas mixtures.
Flammability		: Not available
Lower explosio	n limit	: Not available
Upper explosio	n limit	: Not available
Vapour pressur	re [20°C]	: Not applicable.
Vapour pressur	re [50°C]	: Not applicable.
Density		: Not applicable
Vapour density		Not available
Relative density	y, liquid (water=1)	: Not applicable
Relative densit	y, gas (air=1)	: Heavier than air.
Water solubility	, , , , , , , , , , , , , , , , , , , ,	: Not available
Partition coeffic	cient n-octanol/water (Log Kow)	: Not applicable for gas mixtures.
Auto-ignition te	mperature	: Non flammable.
Decomposition	temperature	: Not available
Viscosity, kiner		: Not applicable.
Particle charac		: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

e.
l

9.2.2. Other safety characteristics



MIGWELD UNIVERSAL

according to Regulation (EU) 2015/830 Reference number: SDS 01115

Evaporation rate Other data

: Not applicable for gas mixtures.

: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity	
10.1. Reactivity	
	No reactivity hazard other than the effects described in sub-sections below.
10.2. Chemical stability	
	Stable under normal conditions.
10.3. Possibility of hazardous reactions	
Reactivity	None. : This mixture contains components with the following reactivity : Violently oxidises organic material.
10.4. Conditions to avoid	
	None.
10.5. Incompatible materials	
	None.
10.6. Hazardous decomposition products	
	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008		
Skin corrosion/irritation	: No known effects from this product.	
Serious eye damage/irritation	: No known effects from this product.	
Respiratory or skin sensitisation	: No known effects from this product.	
Germ cell mutagenicity	: No known effects from this product.	
Carcinogenicity	: No known effects from this product.	
Toxic for reproduction : Fertility	: No known effects from this product.	
Toxic for reproduction : unborn child	: No known effects from this product.	
STOT-single exposure	: No known effects from this product.	
STOT-repeated exposure	: No known effects from this product.	
Aspiration hazard	: Not applicable for gases and gas mixtures.	

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Assessment

EC50 48h - Daphnia magna [mg/l] EC50 72h - Algae [mg/l] LC50 96 h - Fish [mg/l]

- : Classification criteria are not met.
- : No data available.
- : No data available.
- : No data available.



Г

Safety Data Sheet

MIGWELD UNIVERSAL

according to Regulation (EU) 2015/830 Reference number: SDS 01115

Carbon dioxide (124-38-9)	
EC50 48h - Daphnia magna [mg/l]	No data available.
EC50 72h - Algae [mg/l]	No data available.
LC50 96 h - Fish [mg/l]	No data available.
Oxygen (7782-44-7)	
EC50 48h - Daphnia magna [mg/l]	No data available.
EC50 72h - Algae [mg/l]	No data available.
LC50 96 h - Fish [mg/l]	No data available.
Argon (7440-37-1)	
EC50 48h - Daphnia magna [mg/l]	No data available.
EC50 72h - Algae [mg/l]	No data available.
LC50 96 h - Fish [mg/l]	No data available.
12.2. Persistence and degradability	
Assessment	: No data available.
12.3. Bioaccumulative potential	
Assessment	: No data available.
<u>12.4. Mobility in soil</u>	
Assessment	: No data available.
12.5. Results of PBT and vPvB assessment	
Assessment	: Not classified as PBT or vPvB.
12.6. Endocrine disrupting properties	
No additional information available	
12.7. Other adverse effects	
Effect on the ozone layer Effect on global warming	: None. : Contains greenhouse gas(es).

SECTION 13: Disposal considerations

13.1. Waste treatment methods Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at http://www.eiga.org for more guidance on suitable disposal methods. List of hazardous waste codes (from Commission Decision 2000/532/EC as amended) : 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.

13.2. Additional information

None.



an Air Liquide company

Safety Data Sheet

MIGWELD UNIVERSAL

according to Regulation (EU) 2015/830 Reference number: SDS 01115

: 1956

SECTION 14: Transport information

14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN UN-No.

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Transport by sea (IMDG)

: COMPRESSED GAS, N.O.S. (Argon, Carbon dioxide) : Compressed gas, n.o.s. (Argon, Carbon dioxide) : COMPRESSED GAS, N.O.S. (Argon, Carbon dioxide)

14.3. Transport hazard class(es)

Transport by road/rail (ADR/RID)

Transport by air (ICAO-TI / IATA-DGR)

Hazard identification number

Class / Div. (Sub. risk(s))

Transport by sea (IMDG)

Class / Div. (Sub. risk(s))

14.4. Packing group

Transport by sea (IMDG)

Emergency Schedule (EmS) - Fire Emergency Schedule (EmS) - Spillage

Transport by road/rail (ADR/RID)

14.5. Environmental hazards Transport by road/rail (ADR/RID)

Transport by air (ICAO-TI / IATA-DGR)

Labelling

Class

Classification code

Tunnel Restriction



2.2 : Non-flammable, non-toxic gases.

- : 2
- : 1A
- : 20
- : E Passage forbidden through tunnels of category E
- : 2.2
- · 22
- : F-C
- : S-V
- : Not applicable
 - Not applicable
- Not applicable
- · None
 - : None.
 - None.
- 14.6. Special precautions for user

Transport by air (ICAO-TI / IATA-DGR)

Packing Instruction(s)

Transport by sea (IMDG)

Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Passenger and Cargo Aircraft Cargo Aircraft only Transport by sea (IMDG)

Special transport precautions

•

- : P200
- : 200.
- : 200.
- : P200
- : Avoid transport on vehicles where the load space is not separated from the driver's compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

- Before transporting product containers:
- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.



MIGWELD UNIVERSAL

according to Regulation (EU) 2015/830 Reference number: SDS 01115

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information <u>15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture</u>				
			EU-Regulations	
Restrictions on use Other information, restriction and prohibition regulations Seveso Directive : 2012/18/EU (Seveso III)	 Contains no substance on the REACH candidate list Ensure all national/local regulations are observed. Not covered. 			
National regulations				
No additional information available				
15.2. Chemical safety assessment				
	A CSA does not need to be carried out for this product.			

SECTION 16: Other information	
Indication of changes	: Safety data sheet in accordance with commission regulation (EU) No 2020/878.
Training advice Further information	 Receptacle under pressure. This Safety Data Sheet has been established in accordance with the applicable European Union legislation. Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).

Full text of H- and EUH-statements	
H270	May cause or intensify fire; oxidiser.
H280	Contains gas under pressure; may explode if heated.
Ox. Gas 1	Oxidising Gases, Category 1
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas

DISCLAIMER OF LIABILITY

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
 Details given in this document are believed to be correct at the time of going to press.
 Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document