

LASAL 4

SDS_061A_CLP



2.2 : Non flammable, non toxic gas.

Warning



1 Identification of the substance/mixture and of the company/undertaking

Product identifier
Trade name : LASAL 4
SDS Nr : SDS_061A_CLP
Chemical description : Helium
CAS No :007440-59-7
EC No :231-168-5
Index No :---

Chemical formula : He
Registration-No. : Listed in Annex IV / V REACH, exempted from registration.
Use : Industrial and professional. Perform risk assessment prior to use.
Company identification : Energas Ltd.
Westmorland Street, Hull HU2 0HX,
United Kingdom

E-Mail address (competent person): : Mark Nugent
Emergency telephone number : 01482 329333

2 Hazards identification

Classification of the substance or mixture

Hazard Class and Category Code
Regulation EC 1272/2008 (CLP)

• **Physical hazards** : Gases under pressure - Compressed gas - Warning (H280)

Classification EC 67/548 or EC 1999/45 : Not included in Annex VI.
Not classified as dangerous preparation/substance.
No EC labelling required.

Label elements

Labelling Regulation EC 1272/2008 (CLP)

• **Hazard pictograms**



LASAL 4

SDS_061A_CLP

2 Hazards identification (continued)

- Hazard pictograms code : GHS04
- Signal word : Warning
- Hazard statements : H280 : Contains gas under pressure; may explode if heated.
- Precautionary statements
 - Storage : P403 : Store in a well-ventilated place.

Labelling EC 67/548 or EC 1999/45

- Symbol(s) : None.
- R Phrase(s) : None.
- S Phrase(s) : None.

Other hazards

- Other hazards : Asphyxiant in high concentrations.

3 Composition/information on ingredients

Substance / Preparation : Substance.

Substance name	Contents	CAS No	EC No	Index No	Registration no	Classification
Helium	100 %	7440-59-7	231-168-5	----	NOTE 1	Press. Gas (H280) Press. Gas (H280)

Contains no other components or impurities which will influence the classification of the product.

Note 1: Listed in Annex IV / V REACH, exempted from registration.

Note 2: Registration deadline not expired.

Full text of R-phrases see chapter 16

4 First aid measures

First aid measures

- Inhalation : In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- Ingestion : Ingestion is not considered a potential route of exposure.

5 Fire-fighting measures

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : None.
- Extinguishing media
 - Suitable extinguishing media : All known extinguishants can be used.
- Specific methods : If possible, stop flow of product.
Move away from the container and cool with water from a protected position.
- Special protective equipment for fire fighters : In confined space use self-contained breathing apparatus.

LASAL 4

SDS_061A_CLP

6 Accidental release measures

- Personal precautions** : Evacuate area.
Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
Ensure adequate air ventilation.
- Environmental precautions** : Try to stop release.
- Clean up methods** : Ventilate area.

7 Handling and storage

- Handling** : Suck back of water into the container must be prevented.
Do not allow backfeed into the container.
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
Refer to supplier's container handling instructions.
- Storage** : Keep container below 50°C in a well ventilated place.

8 Exposure controls/personal protection

- Personal protection** : Ensure adequate ventilation.

9 Physical and chemical properties

- Physical state at 20 °C** : Gas.
- Colour** : Colourless.
- Odour** : No odour warning properties.
- Molecular weight** : 4
- Melting point [°C]** : Not applicable.
- Boiling point [°C]** : -269
- Critical temperature [°C]** : -268
- Vapour pressure [20°C]** : Not applicable.
- Relative density, gas (air=1)** : 0.14
- Relative density, liquid (water=1)** : Not applicable.
- Solubility in water [mg/l]** : 1.5
- Flammability range [vol% in air]** : Non flammable.

10 Stability and reactivity

- Hazardous decomposition products** : None.
- Chemical stability** : Stable under normal conditions.

11 Toxicological information

- Toxicity information** : No known toxicological effects from this product.

LASAL 4**SDS_061A_CLP****12 Ecological information****Ecological effects information** : No known ecological damage caused by this product.**13 Disposal considerations****General** : Do not discharge into any place where its accumulation could be dangerous.
To atmosphere in a well ventilated place.
Contact supplier if guidance is required.**14 Transport information****UN number** : 1046**• Labelling ADR, IMDG, IATA**

: 2.2 : Non flammable, non toxic gas.

Land transport**ADR/RID****H.I. nr** : 20**UN proper shipping name** : HELIUM, COMPRESSED**Transport hazard class(es)** : 2**- ADR/RID Classification code** : 1 A**- Packing Instruction(s) - General** : P200**- Tunnel Restriction** : E : Passage forbidden through tunnels of category E.**Sea transport****- IMO-IMDG code****• Proper shipping name** : HELIUM, COMPRESSED**• Class** : 2.2**- IMO Packing group** : P200**- Emergency Schedule (EmS) - Fire** : F-C**- Emergency Schedule (EmS) - Spillage** : S-V**- Instructions - Packing** : P200**Air transport****- ICAO/IATA****- Proper shipping name** : HELIUM, COMPRESSED**• Class** : 2.2**• Passenger and Cargo Aircraft** :**- Packing instruction** : 200**• Cargo Aircraft only** :

 <i>an AIR LIQUIDE Group Company</i>	SAFETY DATA SHEET	Page : 5 / 5
		Revised edition no : 0
		Date : 28 / 10 / 2014
		Supersedes : 0 / 0 / 0
LASAL 4		SDS_061A_CLP

14 Transport information (continued)

- Packing instruction : 200

Avoid transport on vehicles where the load space is not separated from the driver's compartment.
 Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Before transporting product containers :

- Ensure that containers are firmly secured.
- Ensure cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.
- Ensure there is adequate ventilation.
- Compliance with applicable regulations.

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture : Ensure all national/local regulations are observed.

Seveso regulation 96/82/EC : Not covered.

16 Other information

Asphyxiant in high concentrations.

Keep container in a well-ventilated place.

Do not breathe the gas.

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws.

DISCLAIMER OF LIABILITY : Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted. Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

End of document