

G26 - 7% Propane,13% Nitrogen in Methane according to Regulation (EU) 2015/830 Reference number: 8578 Issue date: 9/15/2010 Revision date: 8/19/2022 Version: 4.0

Danger



SECTION 1: Identification of the substance/mixture and of the company/undertaking		
1.1. Product identifier		
SDS no	: 8578	
1.2. Relevant identified uses of the substance or	mixture and uses advised against	
Relevant identified uses	 Industrial and professional uses. Perform risk assessment prior to use. Test gas/Calibration gas. Laboratory use. Contact supplier for more information on uses. 	
Uses advised against	: Consumer use.	
1.3. Details of the supplier of the safety data sheet		
Energas Ltd Westmorland Street Hull, HU2 0HX		
1.4. Emergency telephone number		
Emergency telephone number	: 01675 462695 (Available 24/7)	

SECTION 2: Hazards identification

2.1. Classification of t	he substance or mixture	
Classification accordi	ng to Regulation (EC) No. 1272/2008 [CLP]	
Physical hazards	Flammable gases, Category 1A	H220
	Gases under pressure : Compressed gas	H280
2.2. Label elements		
Labelling according to	Regulation (EC) No. 1272/2008 [CLP]	
Hazard pictograms (CLI	P) : GHS02	GHS04
Signal word (CLP)	: Danger	
Hazard statements (CL	P) : H220 - Extrer	nely flammable gas.
	H280 - Conta	ins gas under pressure; may explode if heated.
Precautionary statemen	its (CLP)	
- Prevention	: P210 - Keep No smoking.	away from heat, hot surfaces, sparks, open flames and other ignition sources.
- Response		ng gas fire: Do not extinguish, unless leak can be stopped safely. e of leakage, eliminate all ignition sources.
- Storage		in a well-ventilated place. Protect from sunlight. Store in a well-ventilated place.



G26 - 7% Propane,13% Nitrogen in Methane

according to Regulation (EU) 2015/830 Reference number: 8578

2.3. Other hazards

None.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Methane	CAS-No.: 74-82-8 EC-No.: 200-812-7 EC Index-No.: 601-001-00-4 REACH-no: 01-2119474442-39	80	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
Nitrogen	CAS-No.: 7727-37-9 EC-No.: 231-783-9 EC Index-No.: REACH-no: *1	13	Press. Gas (Comp.), H280
Propane	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944-21	6.3 – 7.7	Flam. Gas 1A, H220 Press. Gas (Liq.), H280

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*3: Registration not required: Substance manufactured or imported < 1t/y.

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation	 Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact	: Adverse effects not expected from this product.
- Eye contact	: Adverse effects not expected from this product.
- Ingestion	: Ingestion is not considered a potential route of exposure.
4.2. Most important symptom	s and effects, both acute and delayed
	In high concentrations may cause asphyxiation. Symptoms may include loss of

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media

: Water spray or fog.



G26 - 7% Propane,13% Nitrogen in

Methane

according to Regulation (EU) 2015/830 Reference number: 8578

5.2. Special hazards arising from the substance or mixture		
Specific hazards Hazardous combustion products	Exposure to fire may cause containers to rupture/explode.Incomplete combustion may form carbon monoxide.	
5.3. Advice for firefighters		
Specific methods	 Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire. Move containers away from the fire area if this can be done without risk. 	
Special protective equipment for fire fighters	 In confined space use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters. 	

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Try to stop release. Evacuate area. Consider the risk of potentially explosive atmospheres. Eliminate ignition sources. Ensure adequate air ventilation. Act in accordance with local emergency plan. Stay upwind.

6.2. Environmental precautions

Try to stop release.

6.3. Methods and material for containment and cleaning up

Ventilate area.

6.4. Reference to other sections

See also sections 8 and 13.



G26 - 7% Propane,13% Nitrogen in

Methane

according to Regulation (EU) 2015/830 Reference number: 8578

SECTION 7: Handling and storage

7.1. Precautions for safe handling	
7.1. Precautions for safe handling Safe use of the product Safe handling of the gas receptacle	 Do not breathe gas. Avoid release of product into atmosphere. The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularily) checked for leaks before use. Do not smoke while handling product. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Assess the risk of potentially explosive atmospheres and the need for explosion-proof equipment. Purge air from system before introducing gas. Take precautionary measures against static discharge. Keep away from ignition sources (including static discharges). Consider the use of only non-sparking tools. Refer to supplier's container handling instructions. Do not allow backfeed into the container. Protect containers from physical damage; do not drag, roll, slide or drop. When moving cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
	Never attempt to transfer gases from one cylinder/container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the content of the container. Containers should be stored in the vertical position and properly secured to prevent them
7.0. Conditions for onfo standard including one in	from falling over.
7.2. Conditions for safe storage, including any in	
7.3 Specific and use(s)	Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials. Segregate from oxidant gases and other oxidants in store. All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere.
7.3. Specific end use(s)	None.



G26 - 7% Propane,13% Nitrogen in

Methane

according to Regulation (EU) 2015/830 Reference number: 8578

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering control	ls
	Provide adequate general and local exhaust ventilation.
	Systems under pressure should be regularily checked for leakages.
	Ensure exposure is below occupational exposure limits (where available).
	Keep concentrations well below lower explosion limits.
	Gas detectors should be used when flammable gases/vapours may be released.
	Consider the use of a work permit system e.g. for maintenance activities.
8.2.2. Individual protection measures	 Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Ensure exposure is below occupational exposure limits (where available). Keep concentrations well below lower explosion limits. Gas detectors should be used when flammable gases/vapours may be released. Consider the use of a work permit system e.g. for maintenance activities. sures, e.g. personal protective equipment A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected. Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications. Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher. Consider the use of flame resistant anti-static safety clothing. Standard EN 1149-5 - Protective clothing: Electrostatic properties. Wear safety shoes while handling containers. Standard EN 1149-5 - Personal protective equipment - Safety footwear. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres. None necessary.
	A risk assessment should be conducted and documented in each work area to assess the
	risks related to the use of the product and to select the PPE that matches the relevant risk.
	The following recommendations should be considered:
	PPE compliant to the recommended EN/ISO standards should be selected.
 Eye/face protection 	: Wear safety glasses with side shields.
	Standard EN 166 - Personal eye-protection - specifications.
Skin protection	
- Hand protection	: Wear working gloves when handling gas containers.
	Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.
- Other	: Consider the use of flame resistant anti-static safety clothing.
	Standard EN ISO 14116 - Limited flame spread materials.
	Standard EN 1149-5 - Protective clothing: Electrostatic properties.
	Wear safety shoes while handling containers.
	Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
 Respiratory protection 	: Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full
Thermal hazards	: None necessary.
8.2.3. Environmental exposure contro	ls
	Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for
	specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Annoaranaa

Appearance	
- Physical state at 20°C / 101.3kPa	: Gas
- Colour	: Mixture contains one or more component(s) which have the following colour(s):
	Colourless.
Odour	: There may be no odour warning properties, odour is subjective and inadequate to warn of
	overexposure.
	Mixture contains one or more component(s) which have the following odour:
	Stenchant often added. Sweetish.
	Odour threshold is subjective and inadequate to warn of overexposure.
	Odour threshold is subjective and inadequate to warn of overexposure.
рН	: Not applicable for gas mixtures.
Melting point / Freezing point	: Not applicable for gas mixtures.
Boiling point	: Not applicable for gas mixtures.
Flash point	: Not applicable for gas mixtures.
Flammability	: Flammability range not available.
Lower explosion limit	: Not available



G26 - 7% Propane,13% Nitrogen in

Methane

according to Regulation (EU) 2015/830 Reference number: 8578

Upper explosion limit	: Not available
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Density	: Not applicable
Vapour density	: Not available
Relative density, liquid (water=1)	: Not applicable
Relative density, gas (air=1)	: Lighter or similar to air.
Water solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for gas mixtures.
Auto-ignition temperature	: Not known.
Decomposition temperature	: Not available
Viscosity, kinematic	: Not applicable.
Particle characteristics	: Not applicable
9.2. Other information	
9.2.1. Information with regard to physical haza	d classes
Explosive properties	: Not applicable.
Oxidising properties	: Not applicable.
9.2.2. Other safety characteristics	
Molar mass	: Not applicable for gas mixtures.
Evaporation rate	: Not applicable for gas mixtures.
Other data	: None.

SECTION 10: Stability and reactivity	
10.1. Reactivity	
	No reactivity hazard other than the effects described in sub-sections below.
10.2. Chemical stability	
	Stable under normal conditions.
10.3. Possibility of hazardous reactions	
	Can form explosive mixture with air. May react violently with oxidants.
Reactivity :	This mixture contains components with the following reactivity : Can form explosive mixture with air. May react violently with oxidants.
10.4. Conditions to avoid	
	Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
10.5. Incompatible materials	
	None.
10.6. Hazardous decomposition products	
	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information		
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008		
Acute toxicity	: Classification criteria are not met.	

Toxicological effects not expected from this product if occupational exposure limit values are



G26 - 7% Propane,13% Nitrogen in

Methane

according to Regulation (EU) 2015/830 Reference number: 8578

Propane (74-98-6)		
LC50 Inhalation - Rat [ppm]		20000 ppm/4h
Skin corrosion/irritation	:	No known effects from this product.
Serious eye damage/irritation	•	No known effects from this product.
Respiratory or skin sensitisation	:	No known effects from this product.
Germ cell mutagenicity	:	No known effects from this product.
Carcinogenicity	:	No known effects from this product.
Toxic for reproduction : Fertility	•	No known effects from this product.
Toxic for reproduction : unborn child	:	No known effects from this product.
STOT-single exposure	:	No known effects from this product.
STOT-repeated exposure	:	No known effects from this product.
Aspiration hazard	:	Not applicable for gases and gas mixtures.
11.2. Information on other hazards		
No additional information available		

SECTION 12: Ecological information

12.1. Toxicity

Assessment	: Classification criteria are not met.
EC50 48h - Daphnia magna [mg/l] EC50 72h - Algae [mg/l] LC50 96 h - Fish [mg/l]	No data available.No data available.No data available.

Propane (74-98-6)

EC50 48h - Daphnia magna [mg/l]	27.1 mg/l
EC50 72h - Algae [mg/l]	11.9 mg/l
LC50 96 h - Fish [mg/l]	49.9 mg/l

Nitrogen (7727-37-9)

EC50 48h - Daphnia magna [mg/l]	No data available.
EC50 72h - Algae [mg/l]	No data available.
LC50 96 h - Fish [mg/l]	No data available.

Methane (74-82-8)	
69.4 mg/l	
19.4 mg/l	
147.5 mg/l	

12.2. Persistence and degradability

Assessment	:	No data available.
12.3. Bioaccumulative potential		
Assessment	:	No data available.



13.1. Waste treatment methods

Safety Data Sheet

G26 - 7% Propane,13% Nitrogen in

Methane

according to Regulation (EU) 2015/830 Reference number: 8578

<u>12.4. Mobility in soil</u>	
Assessment	: No data available.
12.5. Results of PBT and vPvB assessment	
Assessment	: Not classified as PBT or vPvB.
12.6. Endocrine disrupting properties	
No additional information available	
12.7. Other adverse effects	
Effect on the ozone layer	: None.
Effect on global warming	: Contains greenhouse gas(es).
SECTION 13: Disposal considerations	

List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)	 Contact supplier if guidance is required. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at http://www.eiga.org for more guidance on suitable disposal methods. 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.
13.2. Additional information	

None.

SECTION 14: Transport information

14.1. UN number or ID number	
In accordance with ADR / RID / IMDG / IATA / ADN UN-No.	: 1954
14.2. UN proper shipping name	
Transport by road/rail (ADR/RID)	: COMPRESSED GAS, FLAMMABLE, N.O.S. (Methane, Propane)
Transport by air (ICAO-TI / IATA-DGR)	: Compressed gas, flammable, n.o.s. (Methane, Propane)
Transport by sea (IMDG)	: COMPRESSED GAS, FLAMMABLE, N.O.S. (Methane, Propane)
14.3. Transport hazard class(es)	
Labelling	2.1 : Flammable gases.
Transport by road/rail (ADR/RID)	
Class	: 2
Classification code	: 1F
Hazard identification number	: 23
Tunnel Restriction	: B/D - Tank carriage : Passage forbidden through tunnels of category B, C, D and E. Other carriage : Passage forbidden through tunnels of category D and E
Transport by air (ICAO-TI / IATA-DGR)	
Class / Div. (Sub. risk(s))	: 2.1



G26 - 7% Propane,13% Nitrogen in

Methane

according to Regulation (EU) 2015/830 Reference number: 8578

Transport by sea (IMDG)	
Class / Div. (Sub. risk(s))	: 2.1
Emergency Schedule (EmS) - Fire	: F-D
Emergency Schedule (EmS) - Spillage	: S-U
14.4. Packing group	
Transport by road/rail (ADR/RID)	: Not applicable
Transport by air (ICAO-TI / IATA-DGR)	: Not applicable
Transport by sea (IMDG)	: Not applicable
14.5. Environmental hazards	
Transport by road/rail (ADR/RID)	: None.
Transport by air (ICAO-TI / IATA-DGR)	: None.
Transport by sea (IMDG)	: None.
14.6. Special precautions for user	
Packing Instruction(s)	
Transport by road/rail (ADR/RID)	: P200
Transport by air (ICAO-TI / IATA-DGR)	
Passenger and Cargo Aircraft	: Forbidden.
Cargo Aircraft only	: 200.
Transport by sea (IMDG)	: P200
Special transport precautions	: Avoid transport on vehicles where the load space is not separated from the driver's compartment.
	Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in
	the event of an accident or an emergency.
	Before transporting product containers:
	- Ensure there is adequate ventilation.
	- Ensure that containers are firmly secured.
	- Ensure valve is closed and not leaking.

- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

j		
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture		
EU-Regulations		
Restrictions on use Other information, restriction and prohibition regulations Seveso Directive : 2012/18/EU (Seveso III)	 Contains no substance on the REACH candidate list Ensure all national/local regulations are observed. Covered. 	
National regulations No additional information available 15.2. Chemical safety assessment		
	A CSA does not need to be carried out for this product.	

SECTION 16: Other information

Indication of changes

: Safety data sheet in accordance with commission regulation (EU) No 2020/878.



G26 - 7% Propane,13% Nitrogen in

Methane

according to Regulation (EU) 2015/830 Reference number: 8578

Training advice	: Ensure operators understand the flammability hazard. Receptacle under pressure.
Further information	 This Safety Data Sheet has been established in accordance with the applicable European Union legislation. Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).
Full toxt of H and FUH statements	

Full text of H- and EUH-statements	
Flam. Gas 1A	Flammable gases, Category 1A
H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document